

SPEC VANITY I Bath Vanity

52000 / 52002 / 52004 / 52006 / 52008


- cETLus
- Suitable for wet locations
- Dimmable with Triac Dimmer
- Title 24 JA8 Compliant
- Energy Star
- CRI 90+

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

This minimalistic contemporary approach to LED vanity lighting will be the standard for both residential and commercial applications. The light engine features a high quality dimmable driver with multi volt input and high color rendering LEDs for the ultimate vanity lighting.



MEASUREMENTS

MODEL DIMENSION

52000	18"L x 1.75"H x 2.25"EXT
52002	24"L x 1.75"H x 2.25"EXT
52004	30"L x 1.75"H x 2.25"EXT
52006	36"L x 1.75"H x 2.25"EXT
52008	48"L x 1.75"H x 2.25"EXT

HANGING WEIGHT

0.60 LB
0.90 LB
1.45 LB
1.70 LB

LAMPING

MODEL	BULB TYPE	CRI	LUMENS INIT	DEL	COL TEMP.	DIMMABLE	INPUT
52000	(1) 12W PCB LED (Integrated)	90+	840	840	3000K	Triac Dimmer	120-277V
52002	(1) 16W PCB LED (Integrated)	90+	1120	1120	3000K	Triac Dimmer	120-277V
52004	(1) 20W PCB LED (Integrated)	90+	1400	1400	3000K	Triac Dimmer	120-277V
52006	(1) 24W PCB LED (Integrated)	90+	1680	1680	3000K	Triac Dimmer	120-277V
52008	(1) 32W PCB LED (Integrated)	90+	2480	2240	3000K	Triac Dimmer	120-277V

FINISHES OPTIONS:

- Bronze (BZ)
- Polished Chrome (PC)
- Satin Nickel (SN)
- Gold (GLD)



MATERIAL:

Aluminum
 PMMA White Acrylic

RATINGS:

- cETLus
- Wet Location
- Energy Star
- Title 24 JA8 Compliant
- ADA
- Dimmable



ADDITIONAL:

PHOTOMETRIC: Report Found Online
 OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com