





PRODUCT DESCRIPTION

Smaller square profiles extend vertically with light casting both upward and downward. The scale of the product is designed to meet ADA requirements, while providing ample light for outdoor applications. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.

MEASUREMENTS

DIMENSION : 2.5" W x 7.5" H x 3.5" Ext **BACK PLATE** : 4.5" W x 4.5" H x 3.75" HCO

HANGING WEIGHT : 2 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,400 Rated (1,120 Del.)

BULB : 2 x 7W LED DC Integrated , 14W Total

BULB INCLUDED : (Integrated) DIMMABLE : Triac, 0-10V CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION: Up & Down

FINISHES OPTION



MATERIAL

Aluminum, Glass

RATINGS

cETLus Wet Location ADA DARKSKY









ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746